

3250 Linebaugh Rd. Xenia, OH 45385 Telephone (800) 762-0040 FAX (937) 879-8425

CEMENT MILL TEST

Cement Identified as:

Masonry Cement, Type M

Date: 12/01/21

Production Dates:

October, 2021

PHYSICAL REQUIREMENTS	ASTM C 91 SPECIFICATIONS			
	Туре М		RESULTS	
(ASTM C 430) 45-um sieve, % retained	Maximum	24		6
(ASTM C 151) Autoclave Expansion, %	Maximum	1.0		0.12
(ASTM C 266) Time of Setting (Gillmore)				
Initial Set, minutes	Minimum	90		165
Final Set, minutes	Maximum	1000		295
(ASTM C 185) Air Content, %	Range	8-19		14
(ASTM C 1506) Water Retention	Minimum	70		80
(ASTM C 109) Compressive Strength, psi (Mpa)				
7 Day	Minimum	1800 (12.4)		3320 (22.9)
28 Day	Minimum	2900 (20.0)		3960 (27.3)

'We hereby certify that this cement conforms to all of the standard requirements for masonry cement in the above specification for the type specified.

By:

Physical Testing completed by: DG, JT

Chemical Testing completed by: TA, NC, KL, NM

Rusty Strader

Rusty Strader

Quality Control Manager Fairborn Cement Company